

Features

- 30V/160A,
 $R_{DS(ON)} = 1.9m\Omega(Typ.)@V_{GS}=10V$
 $R_{DS(ON)} = 2.8m\Omega(Typ.)@V_{GS}=4.5V$
- Low $R_{DS(ON)}$
- Super High Dense Cell Design
- 100% Avalanche Tested


Applications

- Power Switching Appliaction
- Load Switching



Halogen-Free

Pin Description



Absolute Maximum Ratings

Symbol	Parameter		Rating	Unit
Common Ratings (T _C =25°C Unless Otherwise Noted)				
V _{DSS}	Drain-Source Voltage		30	V
V _{GSS}	Gate-Source Voltage		±20	
T _J	Maximum Junction Temperature		175	°C
T _{STG}	Storage Temperature Range		-55 to 175	°C
I _S	Diode Continuous Forward Current	T _C =25°C	160	A
Mounted on Large Heat Sink				
I _{DP} ^①	300μs Pulse Drain Current Tested	T _C =25°C	640	A
I _D ^②	Continuous Drain Current(V _{GS} =10V)	T _C =25°C	160	A
		T _C =100°C	113	
P _D	Maximum Power Dissipation	T _C =25°C	125	W
		T _C =100°C	62	
R _{θJC}	Thermal Resistance-Junction to Case		1.2	°C/W
R _{θJA} ^③	Thermal Resistance-Junction to Ambient		62.5	°C/W
Drain-Source Avalanche Ratings				
E _{AS} ^④	Avalanche Energy, Single Pulsed		289	mJ


Electrical Characteristics ($T_C=25^{\circ}\text{C}$ Unless Otherwise Noted)

Symbol	Parameter	Test Condition	KS3204GB			Unit
			Min.	Typ.	Max.	
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =250μA	30			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =30V, V _{GS} =0V			1	μA
		T _J =125°C			100	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250μA	1.2	1.7	2.3	V
I _{GSS}	Gate Leakage Current	V _{GS} =±20V, V _{DS} =0V			±100	nA
R _{DS(ON)} ^⑤	Drain-Source On-state Resistance	V _{GS} =10V, I _{DS} =40A		1.9	2.5	mΩ
		V _{GS} =4.5V, I _{DS} =20A		2.8	4	mΩ
Diode Characteristics						
V _{SD} ^⑤	Diode Forward Voltage	I _{SD} =40A, V _{GS} =0V		0.8	1.2	V
t _{rr}	Reverse Recovery Time	I _{SD} =40A, dI _{SD} /dt=100A/μs		59		ns
Q _{rr}	Reverse Recovery Charge			27		nC
Dynamic Characteristics ^⑥						
R _G	Gate Resistance	V _{GS} =0V, V _{DS} =0V, F=1MHz		3.1		Ω
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =15V, Frequency=1.0MHz		4650		pF
C _{oss}	Output Capacitance			685		
C _{rss}	Reverse Transfer Capacitance			560		
t _{d(ON)}	Turn-on Delay Time	V _{DD} =15V, I _{DS} =40A, V _{GEN} =10V, R _G =3Ω		22		ns
t _r	Turn-on Rise Time			19		
t _{d(OFF)}	Turn-off Delay Time			63		
t _f	Turn-off Fall Time			51		
Gate Charge Characteristics ^⑥						
Q _g	Total Gate Charge	V _{DS} =15V, V _{GS} =10V, I _{DS} =40A		68		nC
Q _{gs}	Gate-Source Charge			11		
Q _{gd}	Gate-Drain Charge			15		

- Notes:
- ① Pulse width limited by safe operating area.
 - ② Calculated continuous current based on maximum allowable junction temperature. The package limitation current is 75A.
 - ③ When mounted on 1 inch square copper board, $t \leq 10\text{sec}$. The value in any given application depends on the user's specific board design.
 - ④ Limited by T_{Jmax} , $I_{AS}=34A$, $L=0.5\text{mH}$, $V_{DD}=24V$, $R_G=25\Omega$, Starting $T_J=25^{\circ}\text{C}$, 100% tested and guaranteed.
 - ⑤ Pulse test; Pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.
 - ⑥ Guaranteed by design, not subject to production testing.

Ordering and Marking Information

Device	Package	Packaging	Quantity	Reel Size	Tape width
KS3204GB	TO-263	Tape&Reel	800	13"	24mm




1st Line: Kwansemi LOGO, Kwansemi Code(KS)







2nd Line: Part Number(3204)


3rd Line: Lot Number(YWWXXX)

Typical Characteristics




Typical Characteristics




Package Information
TO-263


SYMBOL	MM			INCH			SYMBOL	MM			INCH		
	MIN	NOM	MAX	MIN	NOM	MAX		MIN	NOM	MAX	MIN	NOM	MAX
A	4.40	4.55	4.72	0.173	0.179	0.186	L	1.94	2.30	2.60	0.076	0.091	0.102
A1	0.00	0.10	0.25	0.000	0.005	0.010	L3	1.17	1.29	1.40	0.046	0.051	0.055
A2	2.59	2.69	2.79	0.102	0.106	0.110	L1	*	*	1.70	*	*	0.067
b	0.76	*	0.90	0.030	*	0.035	L4	0.25 BSC			0.01 BSC		
b1	1.22	*	1.36	0.048	*	0.054	L2	2.50 REF			0.098 REF		
c	0.33	*	0.47	0.013	*	0.019	θ	0°	*	8°	0°	*	8°
c1	1.22	*	1.32	0.048	*	0.052	$\theta 1$	5°	7°	9°	5°	7°	9°
D	8.60	*	9.29	0.339	*	0.366	$\theta 2$	1°	3°	5°	1°	3°	5°
E	9.95	*	10.26	0.392	*	0.404	DEP	0.05	0.10	0.20	0.002	0.004	0.008
e	2.54BSC			0.100BSC			$\Phi p1$	1.40	1.50	1.60	0.055	0.059	0.063
H	14.70	15.10	15.79	0.579	0.594	0.622							


Avalanche Test Circuit and Waveforms




Switching Time Test Circuit and Waveforms



Diode Recovery Test Circuit and Waveforms



Gate Charge Test Circuit and Waveform



Customer Service

Kwansemi Semiconductor Co.,Ltd

Email:Sales@kwansemi.com

Web:www.kwansemi.com

DISCLAIMER:

Kwansemi reserves the right to change the specifications and circuitry without notice at any time. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.