

Features

- 30V/120A,
 $R_{DS(ON)} = 1.4m\Omega(Typ.)@V_{GS}=10V$
 $R_{DS(ON)} = 2.5m\Omega(Typ.)@V_{GS}=4.5V$
- Excellent $Q_G \times R_{DS(on)}$ product(FOM)
- SGT Technology
- 100% Avalanche Tested
- 100% Rg Tested


Applications

- High Frequency Switching and Synchronous Rectification



Halogen-Free

Pin Description



Absolute Maximum Ratings

Symbol	Parameter		Rating	Unit
Common Ratings (T _C =25°C Unless Otherwise Noted)				
V _{DSS}	Drain-Source Voltage		30	V
V _{GSS}	Gate-Source Voltage		±20	
T _{Jmax}	Maximum Junction Temperature		150	°C
T _J , T _{STG}	Operating and Storage Temperature Range		-55 to 150	°C
I _S	Diode Continuous Forward Current	T _C =25°C	120	A
Mounted on Large Heat Sink				
I _{DP} ^①	300μs Pulse Drain Current Tested	T _C =25°C	480	A
I _D ^②	Continuous Drain Current@T _C (V _{GS} =10V)	T _C =25°C	120	A
		T _C =100°C	76	
	Continuous Drain Current@T _A (V _{GS} =10V) ^③	T _A =25°C	38	
		T _A =70°C	31	
P _D	Maximum Power Dissipation@T _C	T _C =25°C	40	W
		T _C =100°C	16	
	Maximum Power Dissipation@T _A ^③	T _A =25°C	4.2	
		T _A =70°C	2.7	

Symbol	Parameter	Rating	Unit
$R_{\theta JC}$	Thermal Resistance-Junction to Case	3.1	°C/W
$R_{\theta JA}^{③}$	Thermal Resistance-Junction to Ambient	30	°C/W
Drain-Source Avalanche Ratings			
$E_{AS}^{④}$	Avalanche Energy, Single Pulsed	225	mJ

Electrical Characteristics ($T_C=25^{\circ}\text{C}$ Unless Otherwise Noted)

Symbol	Parameter	Test Condition	KS3208NUT			Unit
			Min.	Typ.	Max.	
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =250μA	30			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =30V, V _{GS} =0V			1	μA
		T _J =125°C			30	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250μA	1.1	1.8	2.3	V
I _{GSS}	Gate Leakage Current	V _{GS} =±20V, V _{DS} =0V			±100	nA
R _{DS(ON)} ⑤	Drain-Source On-state Resistance	V _{GS} =10V, I _{DS} =20A		1.4	1.7	mΩ
		V _{GS} =4.5V, I _{DS} =15A		2.5	3.3	mΩ
Diode Characteristics						
V _{SD} ⑤	Diode Forward Voltage	I _{SD} =20A, V _{GS} =0V		0.78	1.2	V
t _{rr}	Reverse Recovery Time	I _{SD} =20A, dI _{SD} /dt=100A/μs		18		ns
Q _{rr}	Reverse Recovery Charge			35		nC
Dynamic Characteristics ⑥						
R _G	Gate Resistance	V _{GS} =0V, V _{DS} =0V, F=1MHz		2.3		Ω
C _{ISS}	Input Capacitance	V _{GS} =0V, V _{DS} =15V, Frequency=1.0MHz		2280		pF
C _{OSS}	Output Capacitance			1110		
C _{RSS}	Reverse Transfer Capacitance			140		
t _{d(ON)}	Turn-on Delay Time	V _{DD} =15V, I _{DS} =20A, V _{GS} =10V, R _G =3Ω		13		ns
t _r	Turn-on Rise Time			25		
t _{d(OFF)}	Turn-off Delay Time			42		
t _f	Turn-off Fall Time			15		
Gate Charge Characteristics ⑥						
Q _g	Total Gate Charge	V _{DS} =15V, V _{GS} =10V, I _{DS} =20A		44		nC
Q _{gs}	Gate-Source Charge			6		
Q _{gd}	Gate-Drain Charge			11		

Notes:

- ①Pulse width limited by safe operating area.
- ②Calculated continuous current based on maximum allowable junction temperature. The package limitation current is 50A.
- ③When mounted on 1 inch square copper board, $t \leq 10\text{sec}$.
- ④Limited by $T_{J\text{max}}$, Starting $T_J = 25^\circ\text{C}$, $I_{AS\text{max}} = 30\text{A}$, $L = 0.5\text{mH}$, $V_{DD} = 15\text{V}$, $R_G = 25\Omega$, $V_{GS} = 10\text{V}$. Part not recommended for use above this value. 100% Final Test at $I_{AS} = 16\text{A}$, $L = 0.5\text{mH}$.
- ⑤Pulse test; Pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.
- ⑥Guaranteed by design, not subject to production testing.

Ordering and Marking Information

Device	Package	Packaging	Quantity	Reel Size	Tape width
KS3208NUT	PDFN5060	Tape&Reel	5000	13"	12mm








1st Line: Kwansemi LOGO, Kwansemi Code(KS)







2nd Line: Part Number(3208T)

3rd Line: Lot Number(YWWXXX)

Typical Characteristics




Typical Characteristics



Package Information

PDFN5060




SYMBOL	MM			INCH			SYMBOL	MM			INCH		
	MIN	NOM	MAX	MIN	NOM	MAX		MIN	NOM	MAX	MIN	NOM	MAX
A	0.90	1.00	1.20	0.035	0.039	0.047	E2	3.27	3.50	3.90	0.129	0.138	0.154
b	0.25	*	0.50	0.010	*	0.020	e	1.27BSC			0.050BSC		
c	0.20	0.25	0.30	0.008	0.010	0.012	H	0.41	0.51	0.71	0.016	0.020	0.028
D	5.15BSC			0.203BSC			K	1.10	1.35	1.50	0.043	0.053	0.059
D1	4.80	5.00	5.40	0.189	0.197	0.213	L	0.51	0.61	0.71	0.020	0.024	0.028
D2	3.60	*	4.40	0.142	*	0.173	L1	0.06	0.13	0.30	0.002	0.005	0.012
E	5.90	6.15	6.30	0.232	0.242	0.248	θ	0°	*	12°	0°	*	12°
E1	5.40	5.80	5.95	0.213	0.228	0.234							

- ① Dimensions D1 and E1 do not include mold flash protrusions or gate burrs.
- ② The existence and size of demolding hole are variable depending on mold.
- ③ The size and shape of exposed pad are variable depending on mold.


Avalanche Test Circuit and Waveforms




Switching Time Test Circuit and Waveforms



Diode Recovery Test Circuit and Waveforms



Gate Charge Test Circuit and Waveform



Customer Service

Kwansemi Semiconductor Co., Ltd

Email: Sales@kwansemi.com

Web: www.kwansemi.com

DISCLAIMER:

Kwansemi reserves the right to change the specifications and circuitry without notice at any time. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.