

Features


- 30V/26A,
 $R_{DS(ON)} = 14m\Omega(Typ.)@V_{GS}=10V$
 $R_{DS(ON)} = 18m\Omega(Typ.)@V_{GS}=4.5V$
- Low $R_{DS(ON)}$
- Super High Dense Cell Design
- Fast Switching Speed
- 100% avalanche tested

Applications

- Switching Application Systems



Pin Description



Absolute Maximum Ratings

Symbol	Parameter		Rating	Unit
Common Ratings (T _C =25°C Unless Otherwise Noted)				
V _{DSS}	Drain-Source Voltage		30	V
V _{GSS}	Gate-Source Voltage		±20	
T _J	Maximum Junction Temperature		150	°C
T _{STG}	Storage Temperature Range		-55 to 150	°C
I _S	Diode Continuous Forward Current	T _C =25°C	26	A
Mounted on Large Heat Sink				
I _{DP} ^①	300μs Pulse Drain Current Tested	T _C =25°C	104	A
I _D ^②	Continuous Drain Current@T _C (V _{GS} =10V)	T _C =25°C	26	A
		T _C =100°C	17	
	Continuous Drain Current@T _A (V _{GS} =10V) ^③	T _A =25°C	11	
		T _A =70°C	9	
P _D	Maximum Power Dissipation@T _C	T _C =25°C	21	W
		T _C =100°C	8	
	Maximum Power Dissipation@T _A ^③	T _A =25°C	3.5	
		T _A =70°C	2.3	

Symbol	Parameter	Rating	Unit
$R_{\theta JC}$	Thermal Resistance-Junction to Case	6	$^{\circ}\text{C/W}$
$R_{\theta JA}^{(3)}$	Thermal Resistance-Junction to Ambient	35	$^{\circ}\text{C/W}$
Drain-Source Avalanche Ratings			
$E_{AS}^{(4)}$	Avalanche Energy, Single Pulsed	9	mJ

Electrical Characteristics ($T_C=25^{\circ}\text{C}$ Unless Otherwise Noted)


Symbol	Parameter	Test Condition	KS3240MA			Unit
			Min.	Typ.	Max.	
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =250μA	30			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =30V, V _{GS} =0V			1	μA
		T _J =125°C			30	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250μA	1.1	1.6	2.3	V
I _{GSS}	Gate Leakage Current	V _{GS} =±20V, V _{DS} =0V			±100	nA
R _{DS(ON)} ⑤	Drain-Source On-state Resistance	V _{GS} =10V, I _{DS} =12A		14	18	mΩ
		V _{GS} =4.5V, I _{DS} =10A		18	24	mΩ
Diode Characteristics						
V _{SD} ⑤	Diode Forward Voltage	I _{SD} =12A, V _{GS} =0V		0.88	1.2	V
t _{rr}	Reverse Recovery Time	I _{SD} =12A, dI _{SD} /dt=100A/μs		11		ns
Q _{rr}	Reverse Recovery Charge			16		nC
Dynamic Characteristics ⑥						
R _G	Gate Resistance	V _{GS} =0V, V _{DS} =0V, F=1MHz		1.6		Ω
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =15V, Frequency=1.0MHz		455		pF
C _{oss}	Output Capacitance			75		
C _{rss}	Reverse Transfer Capacitance			60		
t _{d(ON)}	Turn-on Delay Time	V _{DD} =15V, I _{DS} =12A, V _{GS} =10V, R _G =6Ω		8		ns
t _r	Turn-on Rise Time			12		
t _{d(OFF)}	Turn-off Delay Time			27		
t _f	Turn-off Fall Time			9		
Gate Charge Characteristics ⑥						
Q _g	Total Gate Charge	V _{DS} =15V, V _{GS} =10V, I _{DS} =12A		12		nC
Q _{gs}	Gate-Source Charge			3.4		
Q _{gd}	Gate-Drain Charge			4.1		

Notes:

- ①Pulse width limited by safe operating area.
- ②Calculated continuous current based on maximum allowable junction temperature.
- ③When mounted on 1 inch square copper board, $t \leq 10\text{sec}$.
- ④Limited by $T_{J\text{max}}$, $I_{AS} = 6\text{A}$, $L = 0.5\text{mH}$, $V_{DD} = 15\text{V}$, $R_G = 25\Omega$, Starting $T_J = 25^\circ\text{C}$.
- ⑤Pulse test; Pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.
- ⑥Guaranteed by design, not subject to production testing.






Ordering and Marking Information

Device	Package	Packaging	Quantity	Reel Size	Tape width
KS3240MA	PDFN3333	Tape&Reel	5000	13"	12mm










1st Line: Kwansemi Code(KS)
 2nd Line: Part Number(3240)
 3rd Line: Lot Number(YWWXXX)

Typical Characteristics




Typical Characteristics




Package Information
PDFN3333


SYMBOL	MM			INCH			SYMBOL	MM			INCH		
	MIN	NOM	MAX	MIN	NOM	MAX		MIN	NOM	MAX	MIN	NOM	MAX
A	0.67	0.78	0.88	0.026	0.031	0.035	E1	3.05	3.15	3.25	0.120	0.124	0.128
b	0.25	0.30	0.35	0.010	0.012	0.014	E2	2.25	2.45	2.65	0.089	0.096	0.104
c	0.10	0.15	0.25	0.004	0.006	0.010	e	0.65BSC			0.026BSC		
D	3.15	3.35	3.55	0.124	0.132	0.140	H	0.30	0.40	0.50	0.012	0.016	0.020
D1	3.00	3.10	3.20	0.118	0.122	0.126	L	0.30	0.40	0.50	0.012	0.016	0.020
D2	1.53	1.73	1.93	0.060	0.068	0.076	L1	*	0.13	*	*	0.005	*
D3	*	0.13	*	*	0.005	*	θ	*	10°	12°	*	10°	12°
E	3.10	3.30	3.50	0.122	0.130	0.138	M	*	*	0.15	*	*	0.006


Avalanche Test Circuit and Waveforms




Switching Time Test Circuit and Waveforms



Diode Recovery Test Circuit and Waveforms



Gate Charge Test Circuit and Waveform



Customer Service

Kwansemi Semiconductor Co.,Ltd

Email:Sales@kwansemi.com

Web:www.kwansemi.com

DISCLAIMER:

Kwansemi reserves the right to change the specifications and circuitry without notice at any time. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.