

Features

- -16V/-13A,
 $R_{DS(ON)} = 7.5m\Omega(Typ.)@V_{GS}=-4.5V$
 $R_{DS(ON)} = 11m\Omega(Typ.)@V_{GS}=-2.5V$
- Low $R_{DS(ON)}$
- Super High Dense Cell Design
- Reliable and Rugged


Applications

- Load Switch
- PWM Applications
- Power Management



Halogen-Free

Pin Description



Absolute Maximum Ratings

Symbol	Parameter	Rating	Unit
Common Ratings ($T_A=25^{\circ}C$ Unless Otherwise Noted)			
V_{DSS}	Drain-Source Voltage	-16	V
V_{GSS}	Gate-Source Voltage	± 10	
T_{Jmax}	Maximum Junction Temperature	150	$^{\circ}C$
T_J, T_{STG}	Operating and Storage Temperature Range	-55 to 150	$^{\circ}C$
I_S	Diode Continuous Forward Current	$T_A=25^{\circ}C$ -2.9	A
Mounted on Large Heat Sink			
$I_{DP}^{①}$	Pulse Drain Current	$T_A=25^{\circ}C$ -52	A
$I_D^{②}$	Continuous Drain Current($V_{GS}=-4.5V$)	$T_A=25^{\circ}C$ -13	A
		$T_A=70^{\circ}C$ -10	
P_D	Maximum Power Dissipation	$T_A=25^{\circ}C$ 2.5	W
		$T_A=70^{\circ}C$ 1.6	
$R_{\theta JL}$	Thermal Resistance-Junction to Lead	35	$^{\circ}C/W$
$R_{\theta JA}^{③}$	Thermal Resistance-Junction to Ambient	50	$^{\circ}C/W$
Drain-Source Avalanche Ratings			
$E_{AS}^{④}$	Avalanche Energy, Single Pulsed	42	mJ


Electrical Characteristics ($T_A=25^{\circ}\text{C}$ Unless Otherwise Noted)

Symbol	Parameter	Test Condition	KS0320HA			Unit
			Min.	Typ.	Max.	
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =-250μA	-16			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-12V, V _{GS} =0V			-1	μA
		T _J =125°C			-30	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =-250μA	-0.4	-0.7	-1.1	V
I _{GSS}	Gate Leakage Current	V _{GS} =±10V, V _{DS} =0V			±100	nA
R _{DS(ON)} ⑤	Drain-Source On-state Resistance	V _{GS} =-4.5V, I _{DS} =-10A		7.5	10	mΩ
		V _{GS} =-2.5V, I _{DS} =-5A		11	15	mΩ
Diode Characteristics						
V _{SD} ⑤	Diode Forward Voltage	I _{SD} =-10A, V _{GS} =0V		-0.84	-1.2	V
t _{rr}	Reverse Recovery Time	I _{SD} =-10A, dI _{SD} /dt=-100A/μs		21		ns
Q _{rr}	Reverse Recovery Charge			54		nC
Dynamic Characteristics ⑥						
R _G	Gate Resistance	V _{GS} =0V, V _{DS} =0V, F=1MHz		12.7		Ω
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =-8V, Frequency=1MHz		2045		pF
C _{oss}	Output Capacitance			400		
C _{rss}	Reverse Transfer Capacitance			375		
t _{d(ON)}	Turn-on Delay Time	V _{DD} =-8V, I _{DS} =-10A, V _{GEN} =-4.5V, R _G =6Ω		11		ns
t _r	Turn-on Rise Time			18		
t _{d(OFF)}	Turn-off Delay Time			32		
t _f	Turn-off Fall Time			25		
Gate Charge Characteristics ⑥						
Q _g	Total Gate Charge	V _{DS} =-8V, V _{GS} =-4.5V, I _{DS} =-10A		24		nC
Q _{gs}	Gate-Source Charge			3.1		
Q _{gd}	Gate-Drain Charge			6.3		

- Notes:
- ① Pulse width limited by safe operating area.
 - ② Calculated continuous current based on maximum allowable junction temperature.
 - ③ When mounted on 1 inch square copper board, $t \leq 10\text{sec}$. The value in any given application depends on the user's specific board design.
 - ④ Limited by T_{Jmax} , Starting $T_J = 25^{\circ}\text{C}$, $I_{ASmax} = -13A$, $L=0.5\text{mH}$, $V_{DD} = -10V$, $R_G = 25\Omega$, $V_{GS} = -4.5V$. Part not recommended for use above this value.
 - ⑤ Pulse test; Pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.
 - ⑥ Guaranteed by design, not subject to production testing.


Ordering and Marking Information

Device	Package	Packaging	Quantity	Reel Size	Tape width
KS0320HA	SOP8	Tape&Reel	3000	13"	12mm









1st Line: Kwansemi LOGO, Kwansemi Code(KS)
2nd Line: Part Number(0320)
3rd Line: Lot Number(YWWXXX)

Typical Characteristics




Typical Characteristics



Package Information

SOP8




SYMBOL	MM			INCH		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.35	*	1.75	0.053	*	0.069
A1	0.10	*	0.25	0.004	*	0.010
A2	1.25	1.45	1.65	0.049	0.057	0.065
b	0.33	*	0.51	0.013	*	0.020
c	0.15	*	0.25	0.006	*	0.010
D	4.70	4.90	5.10	0.185	0.193	0.201
E	5.80	6.00	6.30	0.228	0.236	0.248
E1	3.80	3.90	4.00	0.150	0.154	0.157
e	1.27BSC			0.050BSC		
L	0.40	*	1.27	0.016	*	0.050
θ	0°	*	8°	0°	*	8°
θ 1	5°	*	15°	5°	*	15°


① Dimensions D and E1 do not include mold flash protrusions or gate burrs.

② The existence and size of demolding hole are variable depending on mold.


Avalanche Test Circuit and Waveforms




Switching Time Test Circuit and Waveforms



Diode Recovery Test Circuit and Waveforms



Gate Charge Test Circuit and Waveform



Customer Service

Kwansemi Semiconductor Co.,Ltd

Email:Sales@kwansemi.com

Web:www.kwansemi.com

DISCLAIMER:

Kwansemi reserves the right to change the specifications and circuitry without notice at any time. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.