

Features


- 40V/190A,
 $R_{DS(ON)} = 2.1m\Omega(Typ.)@V_{GS}=10V$
- Low $R_{DS(ON)}$
- Super High Dense Cell Design
- Fast Recovery Body Diode
- 100% Avalanche Tested

Applications

- Synchronous Rectification
- UPS Inverter
- High efficiency DC/DC Converters



Pin Description



Absolute Maximum Ratings

Symbol	Parameter		Rating	Unit
Common Ratings (T _C =25°C Unless Otherwise Noted)				
V _{DSS}	Drain-Source Voltage		40	V
V _{GSS}	Gate-Source Voltage		±20	
T _J	Maximum Junction Temperature		175	°C
T _{STG}	Storage Temperature Range		-55 to 175	°C
I _S	Diode Continuous Forward Current	T _C =25°C	190	A
Mounted on Large Heat Sink				
I _{DP} ^①	300μs Pulse Drain Current Tested	T _C =25°C	720	A
I _D ^②	Continuous Drain Current(V _{GS} =10V)	T _C =25°C	190	A
		T _C =100°C	134	
P _D	Maximum Power Dissipation	T _C =25°C	176	W
		T _C =100°C	88	
R _{θJC}	Thermal Resistance-Junction to Case		0.85	°C/W
R _{θJA} ^③	Thermal Resistance-Junction to Ambient		62.5	°C/W
Drain-Source Avalanche Ratings				
E _{AS} ^④	Avalanche Energy, Single Pulsed		1500	mJ

Electrical Characteristics ($T_C=25^{\circ}\text{C}$ Unless Otherwise Noted)


Symbol	Parameter	Test Condition	KS4202CA			Unit
			Min.	Typ.	Max.	
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =250μA	40			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =40V, V _{GS} =0V			5	μA
		T _J =125°C			100	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250μA	2		4	V
I _{GSS}	Gate Leakage Current	V _{GS} =±20V, V _{DS} =0V			±100	nA
R _{DS(ON)} ^⑤	Drain-Source On-state Resistance	V _{GS} =10V, I _{DS} =80A		2.1	3	mΩ
Diode Characteristics						
V _{SD} ^⑤	Diode Forward Voltage	I _{SD} =80A, V _{GS} =0V		0.9	1.2	V
t _{rr}	Reverse Recovery Time	I _{SD} =100A, dI _{SD} /dt=100A/μs		77		ns
Q _{rr}	Reverse Recovery Charge			53		nC
Dynamic Characteristics ^⑥						
R _G	Gate Resistance	V _{GS} =0V, V _{DS} =0V, F=1MHz		1.8		Ω
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =20V, Frequency=1.0MHz		5020		pF
C _{oss}	Output Capacitance			790		
C _{rss}	Reverse Transfer Capacitance			290		
t _{d(ON)}	Turn-on Delay Time	V _{DD} =20V, I _{DS} =80A, V _{GEN} =10V, R _G =2.5Ω		19		ns
t _r	Turn-on Rise Time			67		
t _{d(OFF)}	Turn-off Delay Time			49		
t _f	Turn-off Fall Time			31		
Gate Charge Characteristics ^⑥						
Q _g	Total Gate Charge	V _{DS} =20V, V _{GS} =10V, I _{DS} =80A		74		nC
Q _{gs}	Gate-Source Charge			23		
Q _{gd}	Gate-Drain Charge			26		

Notes:

- ① Pulse width limited by safe operating area.
- ② Calculated continuous current based on maximum allowable junction temperature. The package limitation current is 75A.
- ③ When mounted on 1 inch square copper board, $t \leq 10\text{sec}$. The value in any given application depends on the user's specific board design.
- ④ Limited by T_{Jmax} , $I_{AS}=77A$, $L=0.5\text{mH}$, $V_{DD}=24V$, $R_G=25\Omega$, Starting $T_J=25^{\circ}\text{C}$.
- ⑤ Pulse test; Pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.
- ⑥ Guaranteed by design, not subject to production testing.






Ordering and Marking Information

Device	Package	Packaging	Quantity	Reel Size	Tape width
KS4202CA	TO-220	Tube	50	-	-










Y =Year,2017-A,2018-B,etc.
WW =Week.
XXX =Lot number.

Typical Characteristics




Typical Characteristics




Package Information
TO-220


SYMBOL	MM			INCH			SYMBOL	MM			INCH		
	MIN	NOM	MAX	MIN	NOM	MAX		MIN	NOM	MAX	MIN	NOM	MAX
A	4.30	4.54	4.77	0.169	0.179	0.188	$\Phi p1$	1.40	1.50	1.60	0.055	0.059	0.063
A1	1.15	1.30	1.40	0.045	0.051	0.055	e	2.54 BSC			0.10 BSC		
A2	1.90	2.25	2.60	0.075	0.089	0.102	e1	5.08 BSC			0.20 BSC		
b	0.60	0.80	1.00	0.024	0.031	0.039	H1	6.30	6.50	6.80	0.248	0.256	0.268
b2	1.17	1.28	1.72	0.046	0.050	0.068	L	12.70	13.18	13.65	0.500	0.519	0.537
c	0.40	0.50	0.60	0.016	0.020	0.024	L1	*	*	3.95	*	*	0.156
D	15.40	15.70	16.00	0.606	0.618	0.630	L2	2.50 REF			0.098 REF		
D1	8.96	9.21	9.46	0.353	0.363	0.372	Φp	3.50	3.60	3.75	0.138	0.142	0.148
DEP	*	*	0.30	*	*	0.012	Q	2.70	2.80	3.20	0.106	0.110	0.126
E	9.66	9.97	10.28	0.380	0.393	0.405	$\theta 1$	5°	7°	9°	5°	7°	9°
E1	*	8.70	*	*	0.343	*	$\theta 2$	1°	3°	5°	1°	3°	5°
E2	9.80	10.00	10.20	0.386	0.394	0.402							


Avalanche Test Circuit and Waveforms




Switching Time Test Circuit and Waveforms



Diode Recovery Test Circuit and Waveforms



Gate Charge Test Circuit and Waveform



Customer Service

Kwansemi Semiconductor Co.,Ltd

Email:Sales@kwansemi.com

Web:www.kwansemi.com

DISCLAIMER:

Kwansemi reserves the right to change the specifications and circuitry without notice at any time. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.