

Features

- 100V/40A,
 $R_{DS(ON)} = 33m\Omega(Typ.)@V_{GS}=10V$
 $R_{DS(ON)} = 43m\Omega(Typ.)@V_{GS}=4.5V$
- Low $R_{DS(ON)}$
- Super High Dense Cell Design
- Reliable and Rugged


Applications

- Power Switching Appliaction
- Load Switching



Halogen-Free

Pin Description



Absolute Maximum Ratings

Symbol	Parameter		Rating	Unit
Common Ratings (T _C =25°C Unless Otherwise Noted)				
V _{DSS}	Drain-Source Voltage		100	V
V _{GSS}	Gate-Source Voltage		±20	
T _J	Maximum Junction Temperature		175	°C
T _{STG}	Storage Temperature Range		-55 to 175	°C
I _S	Diode Continuous Forward Current	T _C =25°C	40	A
Mounted on Large Heat Sink				
I _{DP} ^①	300μs Pulse Drain Current Tested	T _C =25°C	160	A
I _D ^②	Continuous Drain Current(V _{GS} =10V)	T _C =25°C	40	A
		T _C =100°C	28	
P _D	Maximum Power Dissipation	T _C =25°C	78	W
		T _C =100°C	39	
R _{θJC}	Thermal Resistance-Junction to Case		1.9	°C/W
R _{θJA} ^③	Thermal Resistance-Junction to Ambient		100	°C/W
Drain-Source Avalanche Ratings				
E _{AS} ^④	Avalanche Energy, Single Pulsed		100	mJ


Electrical Characteristics ($T_C=25^{\circ}\text{C}$ Unless Otherwise Noted)

Symbol	Parameter	Test Condition	KS1207DA			Unit
			Min.	Typ.	Max.	
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =250μA	100			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =100V, V _{GS} =0V			1	μA
			T _J =125°C		30	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250μA	1	1.8	2.5	V
I _{GSS}	Gate Leakage Current	V _{GS} =±20V, V _{DS} =0V			±100	nA
R _{DS(ON)} ^⑤	Drain-Source On-state Resistance	V _{GS} =10V, I _{DS} =20A		33	38	mΩ
		V _{GS} =4.5V, I _{DS} =10A		43	46	mΩ
Diode Characteristics						
V _{SD} ^⑤	Diode Forward Voltage	I _{SD} =20A, V _{GS} =0V		0.85	1.2	V
t _{rr}	Reverse Recovery Time	I _{SD} =20A, dI _{SD} /dt=100A/μs		21		ns
Q _{rr}	Reverse Recovery Charge			43		nC
Dynamic Characteristics ^⑥						
R _G	Gate Resistance	V _{GS} =0V,V _{DS} =0V,F=1MHz		1.4		Ω
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =50V, Frequency=1.0MHz		1080		pF
C _{oss}	Output Capacitance			120		
C _{rss}	Reverse Transfer Capacitance			70		
t _{d(ON)}	Turn-on Delay Time	V _{DD} =50V, I _{DS} =20A, V _{GEN} =10V,R _G =6Ω		12		ns
t _r	Turn-on Rise Time			19		
t _{d(OFF)}	Turn-off Delay Time			50		
t _f	Turn-off Fall Time			22		
Gate Charge Characteristics ^⑥						
Q _g	Total Gate Charge	V _{DS} =50V, V _{GS} =10V, I _{DS} =20A		18		nC
Q _{gs}	Gate-Source Charge			2.4		
Q _{gd}	Gate-Drain Charge			4.5		

- Notes:
- ① Pulse width limited by safe operating area.
 - ② Calculated continuous current based on maximum allowable junction temperature.
 - ③ When mounted on 1 inch square copper board, $t \leq 10\text{sec}$. The value in any given application depends on the user's specific board design.
 - ④ Limited by $T_{Jmax}, I_{AS}=20A, L=0.5\text{mH}, V_{DD}=48V, R_G=25\Omega$, Starting $T_J=25^{\circ}\text{C}$.
 - ⑤ Pulse test; Pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.
 - ⑥ Guaranteed by design, not subject to production testing.

Ordering and Marking Information

Device	Package	Packaging	Quantity	Reel Size	Tape width
KS1207DA	TO-252	Tape&Reel	2500	13"	16mm








Y =Year,2017-A,2018-B,etc.







WW =Week.


XXX =Lot number.

Typical Characteristics




Typical Characteristics




Package Information
TO-252


SYMBOL	MM			INCH		
	MIN	NOM	MAX	MIN	NOM	MAX
A	2.200	2.300	2.400	0.087	0.091	0.094
A1	*	*	0.100	*	*	0.004
b	0.660	0.760	0.860	0.026	0.030	0.034
b3	5.130	5.295	5.460	0.202	0.208	0.215
c	0.470	0.535	0.600	0.019	0.021	0.024
D	6.000	6.100	6.200	0.236	0.240	0.244
D1	5.30 REF			0.20 REF		
E	6.500	6.600	6.700	0.256	0.260	0.264
E1	4.700	4.810	4.920	0.185	0.189	0.194
e	2.28 REF			0.09 REF		
H	9.800	10.100	10.400	0.386	0.398	0.409
L	1.400	1.550	1.700	0.055	0.061	0.067
L1	2.743 REF			0.108 REF		
L2	0.510 BSC			0.020 BSC		
L3	0.900	1.075	1.250	0.035	0.042	0.049
L4	0.600	0.800	1.000	0.024	0.031	0.039
θ	0°	*	8°	0°	*	8°
$\theta 1$	5°	7°	9°	5°	7°	9°
$\theta 2$	5°	7°	9°	5°	7°	9°


Avalanche Test Circuit and Waveforms




Switching Time Test Circuit and Waveforms



Diode Recovery Test Circuit and Waveforms



Gate Charge Test Circuit and Waveform



Customer Service

Kwansemi Semiconductor Co.,Ltd

Email:Sales@kwansemi.com

Web:www.kwansemi.com

DISCLAIMER:

Kwansemi reserves the right to change the specifications and circuitry without notice at any time. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.