

Features


- 68V/80A,
 $R_{DS(ON)} = 6.2m\Omega(Typ.)@V_{GS}=10V$
- Low $R_{DS(ON)}$
- Super High Dense Cell Design
- Reliable and Rugged

Applications

- Power Switching Appliaction
- Load Switching



Pin Description



Absolute Maximum Ratings

Symbol	Parameter		Rating	Unit
Common Ratings (T _C =25°C Unless Otherwise Noted)				
V _{DSS}	Drain-Source Voltage		68	V
V _{GSS}	Gate-Source Voltage		±25	
T _J	Maximum Junction Temperature		175	°C
T _{STG}	Storage Temperature Range		-55 to 175	°C
I _S	Diode Continuous Forward Current	T _C =25°C	80	A
Mounted on Large Heat Sink				
I _{DP} ^①	300μs Pulse Drain Current Tested	T _C =25°C	320	A
I _D ^②	Continuous Drain Current(V _{GS} =10V)	T _C =25°C	80	A
		T _C =100°C	56	
P _D	Maximum Power Dissipation	T _C =25°C	107	W
		T _C =100°C	53	
R _{θJC}	Thermal Resistance-Junction to Case		1.4	°C/W
R _{θJA} ^③	Thermal Resistance-Junction to Ambient		100	°C/W
Drain-Source Avalanche Ratings				
E _{AS} ^④	Avalanche Energy, Single Pulsed		400	mJ

Electrical Characteristics ($T_C=25^{\circ}\text{C}$ Unless Otherwise Noted)


Symbol	Parameter	Test Condition	KS6205DB			Unit
			Min.	Typ.	Max.	
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =250μA	68			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =68V, V _{GS} =0V			1	μA
		T _J =125°C			30	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250μA	2	3	4	V
I _{GSS}	Gate Leakage Current	V _{GS} =±25V, V _{DS} =0V			±100	nA
R _{DS(ON)} ^⑤	Drain-Source On-state Resistance	V _{GS} =10V, I _{DS} =40A		6.2	8	mΩ
Diode Characteristics						
V _{SD} ^⑤	Diode Forward Voltage	I _{SD} =40A, V _{GS} =0V		0.89	1.2	V
t _{rr}	Reverse Recovery Time	I _{SD} =40A, dI _{SD} /dt=100A/μs		26		ns
Q _{rr}	Reverse Recovery Charge			35		nC
Dynamic Characteristics ^⑥						
R _G	Gate Resistance	V _{GS} =0V, V _{DS} =0V, F=1MHz		1.8		Ω
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =30V, Frequency=1.0MHz		3290		pF
C _{oss}	Output Capacitance			335		
C _{rss}	Reverse Transfer Capacitance			245		
t _{d(ON)}	Turn-on Delay Time	V _{DD} =30V, I _{DS} =40A, V _{GEN} =10V, R _G =2.5Ω		21		ns
t _r	Turn-on Rise Time			31		
t _{d(OFF)}	Turn-off Delay Time			63		
t _f	Turn-off Fall Time			29		
Gate Charge Characteristics ^⑥						
Q _g	Total Gate Charge	V _{DS} =30V, V _{GS} =10V, I _{DS} =40A		90		nC
Q _{gs}	Gate-Source Charge			18		
Q _{gd}	Gate-Drain Charge			42		

Notes:

- ① Pulse width limited by safe operating area.
- ② Calculated continuous current based on maximum allowable junction temperature. The package limitation current is 60A.
- ③ When mounted on 1 inch square copper board, $t \leq 10\text{sec}$. The value in any given application depends on the user's specific board design.
- ④ Limited by T_{Jmax} , $I_{AS}=40A$, $L=0.5\text{mH}$, $V_{DD}=48V$, $R_G=25\Omega$, Starting $T_J=25^{\circ}\text{C}$.
- ⑤ Pulse test; Pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.
- ⑥ Guaranteed by design, not subject to production testing.

Ordering and Marking Information

Device	Package	Packaging	Quantity	Reel Size	Tape width
KS6205DB	TO-252	Tape&Reel	2500	13"	16mm








Y =Year,2017-A,2018-B,etc.







WW =Week.


XXX =Lot number.

Typical Characteristics




Typical Characteristics




Package Information
TO-252


SYMBOL	MM			INCH		
	MIN	NOM	MAX	MIN	NOM	MAX
A	2.200	2.300	2.400	0.087	0.091	0.094
A1	*	*	0.100	*	*	0.004
b	0.660	0.760	0.860	0.026	0.030	0.034
b3	5.130	5.295	5.460	0.202	0.208	0.215
c	0.470	0.535	0.600	0.019	0.021	0.024
D	6.000	6.100	6.200	0.236	0.240	0.244
D1	5.30 REF			0.20 REF		
E	6.500	6.600	6.700	0.256	0.260	0.264
E1	4.700	4.810	4.920	0.185	0.189	0.194
e	2.28 REF			0.09 REF		
H	9.800	10.100	10.400	0.386	0.398	0.409
L	1.400	1.550	1.700	0.055	0.061	0.067
L1	2.743 REF			0.108 REF		
L2	0.510 BSC			0.020 BSC		
L3	0.900	1.075	1.250	0.035	0.042	0.049
L4	0.600	0.800	1.000	0.024	0.031	0.039
θ	0°	*	8°	0°	*	8°
$\theta 1$	5°	7°	9°	5°	7°	9°
$\theta 2$	5°	7°	9°	5°	7°	9°


Avalanche Test Circuit and Waveforms




Switching Time Test Circuit and Waveforms



Diode Recovery Test Circuit and Waveforms



Gate Charge Test Circuit and Waveform



Customer Service

Kwansemi Semiconductor Co.,Ltd

Email:Sales@kwansemi.com

Web:www.kwansemi.com

DISCLAIMER:

Kwansemi reserves the right to change the specifications and circuitry without notice at any time. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.