


## Features

- 60V/3A,
- $R_{DS(ON)} = 70\text{m}\Omega(\text{Typ.}) @ V_{GS}=10\text{V}$
- $R_{DS(ON)} = 85\text{m}\Omega(\text{Typ.}) @ V_{GS}=4.5\text{V}$
- Low  $R_{DS(ON)}$
- Super High Dense Cell Design
- Reliable and Rugged

## Pin Description



## Applications

- Load Switch



Halogen-Free

## Absolute Maximum Ratings

| Symbol   | Parameter                        | Rating                 | Unit             |
|--|----------------------------------|------------------------|------------------|
| <b>Common Ratings</b> ( $T_A=25^\circ\text{C}$ Unless Otherwise Noted) |                                  |                        |                  |
| $V_{DSS}$  | Drain-Source Voltage             | 60                     | V                |
| $V_{GSS}$  | Gate-Source Voltage              | $\pm 20$               |                  |
| $T_J$  | Maximum Junction Temperature     | 150                    | $^\circ\text{C}$ |
| $T_{STG}$  | Storage Temperature Range        | -55 to 150             | $^\circ\text{C}$ |
| $I_S$  | Diode Continuous Forward Current | $T_A=25^\circ\text{C}$ | 1.3              |
|  |                                  |                        | A                |

### Mounted on Large Heat Sink

|                     |   |                        |      |                    |
|---------------------|---|------------------------|------|--------------------|
| $I_{DP}^{①}$        | 300 $\mu\text{s}$ Pulse Drain Current Tested    | $T_A=25^\circ\text{C}$ | 12   | A                  |
| $I_D^{②}$           | Continuous Drain Current( $V_{GS}=10\text{V}$ ) | $T_A=25^\circ\text{C}$ | 3    | A                  |
|                     |   | $T_A=70^\circ\text{C}$ | 2.4  |                    |
| $P_D$               | Maximum Power Dissipation                       | $T_A=25^\circ\text{C}$ | 1    | W                  |
|                     |   | $T_A=70^\circ\text{C}$ | 0.64 |                    |
| $R_{\theta JC}$     | Thermal Resistance-Junction to Case             | -                      |      | $^\circ\text{C/W}$ |
| $R_{\theta JA}^{③}$ | Thermal Resistance-Junction to Ambient          | 125                    |      | $^\circ\text{C/W}$ |

### Drain-Source Avalanche Ratings

|              |                                 |     |    |
|--------------|---------------------------------|-----|----|
| $E_{AS}^{④}$ | Avalanche Energy, Single Pulsed | TBD | mJ |
|--------------|---------------------------------|-----|----|

**Electrical Characteristics** ( $T_A=25^\circ\text{C}$  Unless Otherwise Noted)

| Symbol  | Parameter                        | Test Condition  | KS6233AB |      |           | Unit             |
|---|----------------------------------|---|----------|------|-----------|------------------|
|   |                                  |   | Min.     | Typ. | Max.      |                  |
| <b>Static Characteristics</b>                     |                                  |   |          |      |           |                  |
| $\text{BV}_{\text{DSS}}$                          | Drain-Source Breakdown Voltage   | $\text{V}_{\text{GS}}=0\text{V}, \text{I}_{\text{DS}}=250\mu\text{A}$   | 60       |      |           | V                |
| $\text{I}_{\text{DSS}}$                           | Zero Gate Voltage Drain Current  | $\text{V}_{\text{DS}}=60\text{V}, \text{V}_{\text{GS}}=0\text{V}$   |          |      | 1         | $\mu\text{A}$    |
|   |                                  | $\text{T}_J=125^\circ\text{C}$  |          |      | 30        |                  |
| $\text{V}_{\text{GS}(\text{th})}$                 | Gate Threshold Voltage           | $\text{V}_{\text{DS}}=\text{V}_{\text{GS}}, \text{I}_{\text{DS}}=250\mu\text{A}$  | 1        | 1.7  | 2.5       | V                |
| $\text{I}_{\text{GSS}}$                           | Gate Leakage Current             | $\text{V}_{\text{GS}}=\pm 20\text{V}, \text{V}_{\text{DS}}=0\text{V}$   |          |      | $\pm 100$ | nA               |
| $\text{R}_{\text{DS}(\text{ON})}^{(5)}$           | Drain-Source On-state Resistance | $\text{V}_{\text{GS}}=10\text{V}, \text{I}_{\text{DS}}=3\text{A}$   |          | 70   | 80        | $\text{m}\Omega$ |
|   |                                  | $\text{V}_{\text{GS}}=4.5\text{V}, \text{I}_{\text{DS}}=2\text{A}$  |          | 85   | 100       | $\text{m}\Omega$ |
| <b>Diode Characteristics</b>                      |                                  |   |          |      |           |                  |
| $\text{V}_{\text{SD}}^{(5)}$                      | Diode Forward Voltage            | $\text{I}_{\text{SD}}=3\text{A}, \text{V}_{\text{GS}}=0\text{V}$  |          | 0.84 | 1.2       | V                |
| $\text{t}_{\text{rr}}$                            | Reverse Recovery Time            | $\text{I}_{\text{SD}}=3\text{A}, \frac{d\text{I}_{\text{SD}}}{dt}=100\text{A}/\mu\text{s}$                              |          | 35   |           | ns               |
| $\text{Q}_{\text{rr}}$                            | Reverse Recovery Charge          |   |          | 12   |           | nC               |
| <b>Dynamic Characteristics</b> <sup>(6)</sup>     |                                  |   |          |      |           |                  |
| $\text{R}_G$                                      | Gate Resistance                  | $\text{V}_{\text{GS}}=0\text{V}, \text{V}_{\text{DS}}=0\text{V}, \text{F}=1\text{MHz}$                                  |          | 1.2  |           | $\Omega$         |
| $\text{C}_{\text{iss}}$                           | Input Capacitance                | $\text{V}_{\text{GS}}=0\text{V}, \text{V}_{\text{DS}}=30\text{V}, \text{Frequency}=1.0\text{MHz}$                       |          | 430  |           | $\text{pF}$      |
| $\text{C}_{\text{oss}}$                           | Output Capacitance               |   |          | 70   |           |                  |
| $\text{C}_{\text{rss}}$                           | Reverse Transfer Capacitance     |   |          | 30   |           |                  |
| $\text{t}_{\text{d}(\text{ON})}$                  | Turn-on Delay Time               | $\text{V}_{\text{DD}}=30\text{V}, \text{I}_{\text{DS}}=3\text{A}, \text{V}_{\text{GEN}}=10\text{V}, \text{R}_G=6\Omega$ |          | 8    |           | ns               |
| $\text{t}_{\text{r}}$                             | Turn-on Rise Time                |   |          | 15   |           |                  |
| $\text{t}_{\text{d}(\text{OFF})}$                 | Turn-off Delay Time              |   |          | 29   |           |                  |
| $\text{t}_{\text{f}}$                             | Turn-off Fall Time               |   |          | 11   |           |                  |
| <b>Gate Charge Characteristics</b> <sup>(6)</sup> |                                  |   |          |      |           |                  |
| $\text{Q}_g$                                      | Total Gate Charge                | $\text{V}_{\text{DS}}=30\text{V}, \text{V}_{\text{GS}}=10\text{V}, \text{I}_{\text{DS}}=3\text{A}$                      |          | 6.3  |           | nC               |
| $\text{Q}_{\text{gs}}$                            | Gate-Source Charge               |   |          | 1.5  |           |                  |
| $\text{Q}_{\text{gd}}$                            | Gate-Drain Charge                |   |          | 1.8  |           |                  |

Notes:

- ①Pulse width limited by safe operating area.

- ②Calculated continuous current based on maximum allowable junction temperature.

- ③When mounted on 1 inch square copper board,  $t \leq 10\text{sec}$ . The value in any given application depends on the user's specific board design.


- ④Limited by  $T_{J\text{max}}$ . Starting  $T_J = 25^\circ\text{C}$ .

- ⑤Pulse test; Pulse width  $\leq 300\mu\text{s}$ , duty cycle  $\leq 2\%$ .

- ⑥Guaranteed by design, not subject to production testing.

**Ordering and Marking Information**






| Device   | Package | Packaging | Quantity | Reel Size | Tape width |
|----------|---------|-----------|----------|-----------|------------|
| KS6233AB | SOT23   | Tape&Reel | 3000     | 7"        | 8mm        |









Y =Year,2017-A,2018-B,etc.


M =Month,Jan-1,Feb-2,...,Sep-9,Oct-A,Nov-B,Dec-C.

## Typical Characteristics



## Typical Characteristics




**Package Information**
**SOT23**


| SYMBOL | MM        |       |       | INCH      |       |       |
|--------|-----------|-------|-------|-----------|-------|-------|
|        | MIN       | NOM   | MAX   | MIN       | NOM   | MAX   |
| A      | 0.900     | 1.025 | 1.150 | 0.035     | 0.040 | 0.045 |
| A1     | 0.050     | 0.075 | 0.100 | 0.002     | 0.003 | 0.004 |
| A2     | 0.900     | 0.975 | 1.020 | 0.035     | 0.038 | 0.040 |
| b      | 0.300     | 0.400 | 0.500 | 0.012     | 0.016 | 0.020 |
| c      | 0.080     | 0.115 | 0.150 | 0.003     | 0.005 | 0.006 |
| D      | 2.800     | 2.900 | 3.000 | 0.110     | 0.114 | 0.118 |
| E      | 1.200     | 1.300 | 1.400 | 0.047     | 0.051 | 0.055 |
| E1     | 2.250     | 2.400 | 2.550 | 0.089     | 0.094 | 0.100 |
| e      | 0.950 TYP |       |       | 0.037 TYP |       |       |
| e1     | 1.800     | 1.900 | 2.000 | 0.071     | 0.075 | 0.079 |
| L      | 0.540 REF |       |       | 0.021 REF |       |       |
| L1     | 0.400     | 0.500 | 0.600 | 0.016     | 0.018 | 0.020 |
| theta  | 0°        | *     | 8°    | 0°        | *     | 8°    |


### Avalanche Test Circuit and Waveforms




### Switching Time Test Circuit and Waveforms



### Diode Recovery Test Circuit and Waveforms



### Gate Charge Test Circuit and Waveform



### Customer Service

Kwansemi Semiconductor Co.,Ltd

Email:[Sales@kwansemi.com](mailto:Sales@kwansemi.com)

Web:[www.kwansemi.com](http://www.kwansemi.com)

### DISCLAIMER:

Kwansemi reserves the right to change the specifications and circuitry without notice at any time. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.