


Features

- 60V/150A,
- $R_{DS(ON)} = 3.5\text{m}\Omega$ (Typ.)@ $V_{GS}=10\text{V}$
- Low $R_{DS(ON)}$
- Super High Dense Cell Design
- High Ruggedness
- 100% Avalanche Tested

Pin Description



Applications

- DC-DC Converters
- Uninterruptible Power Supply



Halogen-Free

Absolute Maximum Ratings

Symbol	Parameter	Rating	Unit
Common Ratings ($T_c=25^\circ\text{C}$ Unless Otherwise Noted)			
V_{DSS}	Drain-Source Voltage	60	V
V_{GSS}	Gate-Source Voltage	± 20	
T_J	Maximum Junction Temperature	175	$^\circ\text{C}$
T_{STG}	Storage Temperature Range	-55 to 175	$^\circ\text{C}$
I_S	Diode Continuous Forward Current	$T_c=25^\circ\text{C}$	150
Mounted on Large Heat Sink			
$I_{DP}^{①}$	300 μs Pulse Drain Current Tested	$T_c=25^\circ\text{C}$	600
$I_D^{②}$	Continuous Drain Current($V_{GS}=10\text{V}$)	$T_c=25^\circ\text{C}$	150
		$T_c=100^\circ\text{C}$	106
P_D	Maximum Power Dissipation	$T_c=25^\circ\text{C}$	188
		$T_c=100^\circ\text{C}$	94
$R_{\theta JC}$	Thermal Resistance-Junction to Case	0.8	$^\circ\text{C/W}$
$R_{\theta JA}^{③}$	Thermal Resistance-Junction to Ambient	62.5	$^\circ\text{C/W}$
Drain-Source Avalanche Ratings			
$E_{AS}^{④}$	Avalanche Energy, Single Pulsed	506	mJ


Electrical Characteristics ($T_C=25^\circ\text{C}$ Unless Otherwise Noted)

Symbol	Parameter	Test Condition	KS6203GA			Unit
			Min.	Typ.	Max.	
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_{\text{DS}}=250\mu\text{A}$	60			V
I_{DSS}	Zero Gate Voltage Drain Current	$\text{V}_{\text{DS}}=60\text{V}, \text{V}_{\text{GS}}=0\text{V}$			1	μA
		$\text{T}_J=125^\circ\text{C}$			30	
$\text{V}_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$\text{V}_{\text{DS}}=\text{V}_{\text{GS}}, \text{I}_{\text{DS}}=250\mu\text{A}$	2	3	4	V
I_{GSS}	Gate Leakage Current	$\text{V}_{\text{GS}}=\pm 20\text{V}, \text{V}_{\text{DS}}=0\text{V}$			± 100	nA
$\text{R}_{\text{DS}(\text{ON})}$ ^⑤	Drain-Source On-state Resistance	$\text{V}_{\text{GS}}=10\text{V}, \text{I}_{\text{DS}}=40\text{A}$		3.5	5	mΩ
Diode Characteristics						
V_{SD} ^⑤	Diode Forward Voltage	$\text{I}_{\text{SD}}=40\text{A}, \text{V}_{\text{GS}}=0\text{V}$		0.85	1.2	V
t_{rr}	Reverse Recovery Time	$\text{I}_{\text{SD}}=40\text{A}, \frac{d\text{I}_{\text{SD}}}{dt}=100\text{A}/\mu\text{s}$		48		ns
Q_{rr}	Reverse Recovery Charge			99		nC
Dynamic Characteristics ^⑥						
R_G	Gate Resistance	$\text{V}_{\text{GS}}=0\text{V}, \text{V}_{\text{DS}}=0\text{V}, \text{F}=1\text{MHz}$		2.3		Ω
C_{iss}	Input Capacitance	$\text{V}_{\text{GS}}=0\text{V}, \text{V}_{\text{DS}}=30\text{V}, \text{Frequency}=1.0\text{MHz}$		6130		pF
C_{oss}	Output Capacitance			955		
C_{rss}	Reverse Transfer Capacitance			560		
$\text{t}_{\text{d}(\text{ON})}$	Turn-on Delay Time	$\text{V}_{\text{DD}}=30\text{V}, \text{I}_{\text{DS}}=40\text{A}, \text{V}_{\text{GEN}}=10\text{V}, \text{R}_G=6\Omega$		17		ns
t_{r}	Turn-on Rise Time			51		
$\text{t}_{\text{d}(\text{OFF})}$	Turn-off Delay Time			39		
t_{f}	Turn-off Fall Time			15		
Gate Charge Characteristics ^⑥						
Q_{g}	Total Gate Charge	$\text{V}_{\text{DS}}=30\text{V}, \text{V}_{\text{GS}}=10\text{V}, \text{I}_{\text{DS}}=40\text{A}$		95		nC
Q_{gs}	Gate-Source Charge			19		
Q_{gd}	Gate-Drain Charge			24		

- Notes:
- ①Pulse width limited by safe operating area.
 - ②Calculated continuous current based on maximum allowable junction temperature. The package limitation current is 75A.
 - ③When mounted on 1 inch square copper board, $t \leq 10\text{sec}$. The value in any given application depends on the user's specific board design.
 - ④Limited by $T_{J,\text{max}}$, $\text{I}_{\text{AS}} = 45\text{A}$, $L=0.5\text{mH}$, $\text{V}_{\text{DD}} = 48\text{V}$, $\text{R}_G = 25\Omega$, Starting $T_J = 25^\circ\text{C}$.
 - ⑤Pulse test; Pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.
 - ⑥Guaranteed by design, not subject to production testing.

Ordering and Marking Information

Device	Package	Packaging	Quantity	Reel Size	Tape width
KS6203GA	TO-263	Tape&Reel	800	13"	24mm








1st Line: Kwansemi LOGO, Kwansemi Code(KS)







2nd Line: Part Number(6203)


3rd Line: Lot Number(YWWXXX)

Typical Characteristics



Typical Characteristics



Package Information
TO-263


SYMBOL	MM			INCH			SYMBOL	MM			INCH		
	MIN	NOM	MAX	MIN	NOM	MAX		MIN	NOM	MAX	MIN	NOM	MAX
A	4.40	4.55	4.72	0.173	0.179	0.186	L	1.94	2.30	2.60	0.076	0.091	0.102
A1	0.00	0.10	0.25	0.000	0.005	0.010	L3	1.17	1.29	1.40	0.046	0.051	0.055
A2	2.59	2.69	2.79	0.102	0.106	0.110	L1	*	*	1.70	*	*	0.067
b	0.76	*	0.90	0.030	*	0.035	L4	0.25 BSC			0.01 BSC		
b1	1.22	*	1.36	0.048	*	0.054	L2	2.50 REF			0.098 REF		
c	0.33	*	0.47	0.013	*	0.019	θ	0°	*	8°	0°	*	8°
c1	1.22	*	1.32	0.048	*	0.052	θ1	5°	7°	9°	5°	7°	9°
D	8.60	*	9.29	0.339	*	0.366	θ2	1°	3°	5°	1°	3°	5°
E	9.95	*	10.26	0.392	*	0.404	DEP	0.05	0.10	0.20	0.002	0.004	0.008
e	2.54BSC			0.100BSC			Φp1	1.40	1.50	1.60	0.055	0.059	0.063
H	14.70	15.10	15.79	0.579	0.594	0.622							


Avalanche Test Circuit and Waveforms




Switching Time Test Circuit and Waveforms



Diode Recovery Test Circuit and Waveforms



Gate Charge Test Circuit and Waveform



Customer Service

Kwansemi Semiconductor Co.,Ltd

Email:Sales@kwansemi.com

Web:www.kwansemi.com

DISCLAIMER:

Kwansemi reserves the right to change the specifications and circuitry without notice at any time. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.