

Features

- 120V/115A,
 $R_{DS(ON)} = 5.4m\Omega(Typ.)@V_{GS}=10V$
 $R_{DS(ON)} = 6.9m\Omega(Typ.)@V_{GS}=4.5V$
- Excellent $Q_G \times R_{DS(on)}$ product(FOM)
- SGT Gen2 Technology
- High Ruggedness
- 100% Avalanche Tested


Applications

- High Frequency Switching and Synchronous Rectification
- Switch Mode Power Supply



Halogen-Free

Pin Description



Absolute Maximum Ratings

Symbol	Parameter	Rating	Unit
Common Ratings ($T_C=25^\circ\text{C}$ Unless Otherwise Noted)			
V_{DSS}	Drain-Source Voltage	120	V
V_{GSS}	Gate-Source Voltage	± 20	
T_{Jmax}	Maximum Junction Temperature	175	$^\circ\text{C}$
T_J, T_{STG}	Operating and Storage Temperature Range	-55 to 175	$^\circ\text{C}$
I_S	Diode Continuous Forward Current	$T_C=25^\circ\text{C}$	115 A
Mounted on Large Heat Sink			
$I_{DP}^{①}$	300 μs Pulse Drain Current Tested	$T_C=25^\circ\text{C}$	460 A
$I_D^{②}$	Continuous Drain Current($V_{GS}=10V$)	$T_C=25^\circ\text{C}$	115 A
		$T_C=100^\circ\text{C}$	81 A
P_D	Maximum Power Dissipation	$T_C=25^\circ\text{C}$	192 W
		$T_C=100^\circ\text{C}$	96 W
$R_{\theta JC}$	Thermal Resistance-Junction to Case	0.78	$^\circ\text{C/W}$
$R_{\theta JA}^{③}$	Thermal Resistance-Junction to Ambient	62.5	$^\circ\text{C/W}$
Drain-Source Avalanche Ratings			
$E_{AS}^{④}$	Avalanche Energy, Single Pulsed	420	mJ


Electrical Characteristics ($T_C=25^\circ\text{C}$ Unless Otherwise Noted)

Symbol	Parameter	Test Condition	KSA202CAT2			Unit
			Min.	Typ.	Max.	
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_{DS}=250\mu A$	120			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=120V, V_{GS}=0V$			1	μA
		$T_J=125^\circ\text{C}$			30	
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_{DS}=250\mu A$	1.2	1.8	2.3	V
I_{GSS}	Gate Leakage Current	$V_{GS}=\pm 20V, V_{DS}=0V$			± 100	nA
$R_{DS(ON)}^{(5)}$	Drain-Source On-state Resistance	$V_{GS}=10V, I_{DS}=20A$		5.4	6.5	$m\Omega$
		$V_{GS}=4.5V, I_{DS}=15A$		6.9	9	$m\Omega$
Diode Characteristics						
$V_{SD}^{(5)}$	Diode Forward Voltage	$I_{SD}=20A, V_{GS}=0V$		0.81	1.2	V
t_{rr}	Reverse Recovery Time	$I_{SD}=20A, dI_{SD}/dt=100A/\mu s$		42		ns
Q_{rr}	Reverse Recovery Charge			57		nC
Dynamic Characteristics⁽⁶⁾						
R_G	Gate Resistance	$V_{GS}=0V, V_{DS}=0V, F=1\text{MHz}$		0.9		Ω
C_{iss}	Input Capacitance	$V_{GS}=0V,$ $V_{DS}=60V,$ Frequency=1.0MHz		3210		pF
C_{oss}	Output Capacitance			790		
C_{rss}	Reverse Transfer Capacitance			20		
$t_{d(ON)}$	Turn-on Delay Time			11		
t_r	Turn-on Rise Time	$V_{DD}=60V, I_{DS}=20A,$ $V_{GEN}=10V, R_G=3\Omega$		34		
$t_{d(OFF)}$	Turn-off Delay Time			45		
t_f	Turn-off Fall Time			22		
Gate Charge Characteristics⁽⁶⁾						
Q_g	Total Gate Charge	$V_{DS}=60V, V_{GS}=10V,$ $I_{DS}=20A$		47		nC
Q_{gs}	Gate-Source Charge			11		
Q_{gd}	Gate-Drain Charge			7		

- Notes:
- ① Pulse width limited by safe operating area.
 - ② Calculated continuous current based on maximum allowable junction temperature. The package limitation current is 75A.
 - ③ When mounted on 1 inch square copper board, $t \leq 10\text{sec}$. The value in any given application depends on the user's specific board design.
 - ④ Limited by T_{Jmax} , Starting $T_J = 25^\circ\text{C}$, $I_{ASmax} = 41A$, $L = 0.5\text{mH}$, $V_{DD} = 48V$, $R_G = 25\Omega$, $V_{GS} = 10V$. Part not recommended for use above this value. 100% Final Test at $I_{AS} = 28A$, $L = 0.5\text{mH}$.
 - ⑤ Pulse test; Pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.
 - ⑥ Guaranteed by design, not subject to production testing.






Ordering and Marking Information

Device	Package	Packaging	Quantity	Reel Size	Tape width
KSA202CAT2	TO-220	Tube	50	-	-









- 1st Line: Kwansemi LOGO, Kwansemi Code(KS)
2nd Line: Part Number(A202T)
3rd Line: Lot Number(YWWXXX)

Typical Characteristics




Typical Characteristics



Package Information

TO-220



SYMBOL	MM			INCH			SYMBOL	MM			INCH		
	MIN	NOM	MAX	MIN	NOM	MAX		MIN	NOM	MAX	MIN	NOM	MAX
A	4.30	4.55	4.80	0.169	0.179	0.189	E1	7.00	*	8.40	0.276	*	0.331
A1	1.20	1.30	1.45	0.047	0.051	0.057	E2	*	*	0.75	*	*	0.030
A2	2.20	2.40	2.70	0.087	0.094	0.106	e	2.54BSC			0.100BSC		
b	0.70	0.80	0.95	0.028	0.031	0.037	e1	5.08BSC			0.200BSC		
b2	1.15	1.35	1.50	0.045	0.053	0.059	H1	6.30	6.50	6.80	0.248	0.256	0.268
c	0.40	0.50	0.60	0.016	0.020	0.024	L	12.70	13.20	13.90	0.500	0.520	0.547
D	15.10	15.60	16.10	0.594	0.614	0.634	L1	2.85	*	3.50	0.112	*	0.138
D1	8.75	9.20	9.65	0.344	0.362	0.380	ΦP	3.50	3.65	3.80	0.138	0.144	0.150
D2	12.20	12.50	12.80	0.480	0.492	0.504	Q	2.70	*	2.90	0.106	*	0.114
E	9.70	10.00	10.30	0.382	0.394	0.406							

① Dimensions D and D1 and E do not include mold flash protrusions or gate burrs.

② The existence and size of demolding hole are variable depending on mold.

Avalanche Test Circuit and Waveforms



Switching Time Test Circuit and Waveforms



Diode Recovery Test Circuit and Waveforms



Gate Charge Test Circuit and Waveform



Customer Service

Kwansemi Semiconductor Co.,Ltd

Email:Sales@kwansemi.com

Web:www.kwansemi.com

DISCLAIMER:

Kwansemi reserves the right to change the specifications and circuitry without notice at any time. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.